

APPENDIX A

Pseudo-Code for the Invention

```
5  /*      Load existing document database into memory.
    The data structure used is a hash with each hash value pointing to a balanced tree
    containing the ordered pair (Digest, DocId). The data structure is searched via the digest
    value. */
    DigestDB = LoadDocDB ( dbname ) ;

10 /*      Load the list of stop words to ignore and create a hash table.
    -- This step is optional if the user does not desire stop word removal      */
    stopwordHash = LoadStopWordList (filename) ;

    /*      Get a list of new documents to process.      */
15 DocsToProcess = GetDocsToProcess (processlist) ;

    /*      Get first document to process.      */
    DocToParse = DocsToProcess.nextDoc() ;

20 /*      Continue as long as there are documents to process */
    While ( DocToParse )
    {
        /*      Create SHA1 Digest Object for current document      */
        SHA1 sha1 = new SHA1() ; //

25        /*      Create Parser Object for current document      */
        Parser parser = new Parser(DocToParse) ;

        /*      The derived tree represents all the unique tokens from the current document.
            The tree is ordered in Unicode ascending order      */
30        Tree docTokens = new Tree() ;

        /*      Continue iteration for as long as there are tokens to process */
        for ( ;; )
35        {
            /*      Get the next token from the document      */
            token = parser.getNext() ;

            /*      If there are no more tokens to process, exit loop      */
40            if ( token == null ) break ;

            /*      Using term thresholds, retain only significant tokens.
                If parts of speech are used, remove the ignored parts of speech.
                In the pseudo-code, only the removal of stop words are illustrated. If
45                other text components are to be removed, they should be removed at this
```

